

Quality by Design



WWW.TRILO.COM

SG 1170 G



SG 1100 G



SG 1165 K

Grass Collection

SG 1100 G and SG 1170 G

FIRST CLASS TURF

If you are concerned with the care of golf courses or the production of acres of turf, you want equipment that makes impressions on your work load, not impressions like ruts and tyre marks! That's why the Trilo Grass Collectors are ideal for you.

POWERFUL

The heart of the machine is formed by a high capacity fan giving it a high work rate enabling you to collect large amounts of clippings. The reinforced, balanced fan wheel and the double walled casing provide a wear resistant, reliable and above all safe source of suction power.



The Trilo Grass Collectors fully floating 3.00 m brush hood with variable depth setting, which is perfectly capable of working in the dampest conditions, allows you to achieve the quality you want.



SCARIFY AND CLEAN

One of the problems facing quality turf production is thatch. It builds into a solid layer preventing fresh growth. TRILO's 2 m wide flexible scarifier breaks up this cake and enables it to be collected, so freeing fresh shoots to develop and grow.



F MACHINES

SG 1165 K

For over 30 years TRILO have been listening to their clients, always developing and improving their range of vacuum sweepers making the market leader.

The TRILO SG1165K is the biggest Grass Collector ever built. It had a working width of 6.5 metres, more than doubling the largest currently available. With combination of vacuum and brush it will clear 20 acres an hour.

Designed for the larger turf producer it ensures that grass cutting collection, a vital part of top quality turf production, is done more efficiently than ever, allowing one machine, tractor and driver to do more than two could previously. This will help keep the production costs down.



LOW GROUND PRESSURE

The machine is provided with dual pendling wheels size 19.00/55x17-10ply to avoid tyre marks on your turf. This unique machine with its wide tyres performs efficiently

even in wet conditions. The centre hood is lifted hydraulically and the two 2.5 metre wings fold up for transport making traveling from field to field easy.





SG 1170 G

Fan size mm	• ø 960/4
PTO shaft	• 540 rpm
kW requested	• > 38
Length m	• 5,10
Width m	• 1,75
Height m	• 2,05
Working width m	• 2,00-2,50-3,00
Loading cap.m ³	• 7
Operating weight	• 1.530 kg
Tyres	• 19.55x17-10 ply
Hydraulic system	• 180 bar - 40 ltr/min



SG 1100 G

Fan size mm	• ø 960/4
PTO shaft	• 540 rpm
kW requested	• > 38
Length m	• 6,30
Width m	• 1,75
Height m	• 2,45
Working width m	• 2,00-2,50-3,00
Loading cap.m ³	• 11
Operating weight	• 1.800 kg
Tyres	• 19.55x17-10 ply
Hydraulic system	• 180 bar - 40 ltr/min



SG 1165 K

Fan size mm	• ø 960/4
PTO shaft	• 540 rpm
kW requested	• > 38
Length m	• 6,30
Width m	• 2,10
Height m	• 2,28
Working width m	• 6,50
Loading cap.m ³	• 11
Operating weight	• 2.400 kg
Dual pending wheels	• 19.55x17-10 ply
Hydraulic system	• 180 bar - 40 ltr/min



DEALER:

Trilo CE Made in Holland



Astronaut 40

NL - 3824 MJ Amersfoort

Tel.: (+31) (0)33 456 44 32

Fax: (+31) (0)33 456 44 33

E-mail: Sales@trilo.com

WWW.TRILO.COM