

HARVESTERS

SH 1576

SOD HARVESTER

Setting New Standards Worldwide
Turf Industry Leaders in Service and Innovation



WE'RE COMMITTED TO IMPROVING YOUR HARVEST.

Features:

- Heavy-duty cutting head frame
- Independent floating cutting head
- Can harvest 16", 18", or 24" widths in 18" to 100" lengths. Rolls or Slabs
- Optional brush attachment keeps turf free of debris and clippings
- Quick, easy cut-off spring tension adjustment
- New exclusive Brouwer low-profile rubber mat with polyethylene sliders is gentle on turf
- No waste: cuts close to pipes, fences and ditches
- Optional 4 wheel drive
- Independently mounted Curved or Cross Conveyors
- Conveyor front weight bar, standard
- Works well in all soil conditions
- Hydraulic flap control (Roll)



Specifications:

WIDTH OF CUT

12" (305mm) 16" (406mm) 18" (457mm)
23" (584mm) 24" (610mm)

LENGTH OF CUT

24" (610 mm) to 100" (2540 mm)

PERFORMANCE

1500 sq. yd. (1260 m/sq.) per hour.

THICKNESS OF CUT

Power Adjustable to 2 1/8" (54 mm)

OPERATING DIMENSIONS

L. 176 in. (4470 mm.) W. 120 in. (3048 mm.)
H. 104 in. (2641 mm.)

WEIGHT

John Deere 2WD 11318 lbs. John Deere 4WD 11863 lbs.



KESMAC INC.
TEL: 905-476-6222 • 1-888-341-5113 FAX: 905-476-6744
US Parts TEL: 1-800-314-1008
23324 Woodbine Avenue, Keswick, Ontario L4P 3E9
email: info@kesmac.com • www.brouwerturf.com



Specifications subject to change without notice or obligation.
Printed in Canada 01/16